

DUBUQUE FAIRGROUNDS RC RACEWAY 2021-2022

GENERAL RULES

- 1) NO illegal substances or alcoholic beverages are permitted at any DFRCR racing event.
- 2) Foul language, aggressive or abusive behavior will not be tolerated.
- 3) Remember this is supposed to be fun. **Physical contact/ Slandering of any kind may result in loss of all points and a 1 year suspension from date of infraction, from all DFRCR sanctioned events.**
- 4) Race director and/or computer operator and Drivers should not be distracted during races.
- 5) Race director reserves the right to "black flag" any drivers who are operating in a reckless or uncontrolled manner or that may constitute a hazard to other drivers in a race.
- 6) If you leave the driver's stand during a race, you should not return to the race. When exiting the driver's stand, no driver shall walk across the race track or in front of other drivers.
- 7) You must corner marshal the race following your race. If a substitute is needed due to physical or other reasons, it is your responsibility to arrange for a substitute.
- 8) Corner marshals must pay attention to their area and be ready to give assistance or remove cars from the track.
- 9) Corner marshals must remain near the track until the race is done.
- 10) Disputes will be resolved by the Race Director and/or Race Committee. All decisions are final.
- 11) All classes of racing, unless noted, will run a maximum of a 2 cell lipo battery in a hard case or max. 7 cell NiMH battery. Lipo batteries must not be charged above the ROAR charge limit of 4.22 per cell max. All battery packs should be charged inside a "LiPo Sack" or similar fire mitigation device proven to withstand a minimum of a 7.4v 10,000mah Lithium Polymer pack failing destructively without showing external flame. All Batteries must have a quick release plug-in. 1/8 scale has a maximum of 3 cells lipo.
- 12) **"VIP"** stands for **V**oltage **I**nspection **P**ort. A **"VIP"** may be required in some classes. It is simply a servo extension cable with the male connector removed and is soldered to the positive and negative posts on esc or esc connector. The female end is then attached (shoe good) to the chasses in a position that is easy to access with the body on. The **"VIP"** purpose is for the ease of checking the pack voltage before a race, i.e. to check for overcharging of batteries. If battery is over charged (above 8.44) the car/truck will not race until its voltage is below the charge limit (i.e. voltage must show 8.43 or below) on whatever device (dvm, battery bug, etc.) the track is using to monitoring battery voltage with.
- 13) No hybrid or modified rotors in any brushed or brushless motors.
- 14) No mechanical, adjustable wings from radio, no front brakes allowed.
- 15) No BLUE TOOTH / WIFI connection devices allowed in race cars/trucks that will allow for adjustments to the ESC remotely. This applies to classes that are running sportsman (Blinky Mode) ESC. If the connection device is in your car/truck it must be un-plugged and disabled.
- 16) All cars/trucks, that are running in a class that requires a sportsman type ESC could be checked for sportsman setting (Blinky Mode) at any time before or after a race.
- 17) No drive assist / traction control systems. The Traxxas receiver #6533 (see picture below) is **NOT** legal for use (i.e. cannot be in your race car/truck) in any class of racing except **novice class** (i.e. gyros, TSM, or any drive assist systems, if built in to radio system it must be disable).
- 18) All cars/trucks must have working brakes (drive wheels stop moving when throttle trigger is moved forward), and reverse must be disabled. This is in all classes of racing.
- 19) All racers must sign a liability waiver the first time they race each season and they will receive a set of track rules at that time. Racers under the age of 18 must have the waiver signed by a parent or guardian.
- 20) All cars should be numbered.
- 21) ****3 FOOT RULE**** All race cars/trucks must wipe excess tire compound/treatment off of their tires before entering race track. This is to ensure an equal racing surface for all classes. Any car that leaves a longer than a 3 FOOT wet track from tires will be DISQUALIFIED from that race.
- 22) **FOAM TIRES ARE NOT ALLOWED ON THE DIRT TRACK IN ANY CLASS OF RACING.**
- 23) Rules are subject to change.
- 24) If it doesn't say you can do it in the rules then you cannot do it.



not legal



legal

COMPETITION AND PRIZES

- DFRCR will sponsor individual race prizes, point series, and season championships to promote competition among participants. For a racing class to be eligible for series and season championships, at least five racers in each class must complete at least 2/3 of the available races in the series or season. Race Committee will designate the series and number of races within the series that will count towards prizes.

RACE PROGRAM

- All race day programs consist of two qualifiers and mains.
- No substitute drivers in the mains.
- You must race the car that you qualified with and start in the correct qualifying spot.
- Minimum of (2) cars in a class. Race Director can combine classes of similar speed to maintain a smooth running program.
- Drivers need to supply their own personal transponder. It is the driver's responsibility to check their transponder for proper functionality before races start.
- Race Director / computer operator will not be responsible to hand count cars that do not pass the scoring loop or do not count due to any type of transponder failure.
- Qualifiers and Mains will use either "rolling" (IFMAR) or "standing" starts.

ALL 2WD CLASSES LISTED BELOW: All entries must be 2wd, rear wheel drive only unless the class calls for it to be a 4WD class. For turn marshal safety, all cars must have a front bumper that is made of a shock absorbing material. Front bumpers must be mounted in such a way that they will contact an object prior to any other portion of the car in a front impact. All late model, modified, and sprint car bodies and cages must resemble contemporary full scale cars racing in the "World of Outlaws", "IMCA" and "DIRT" sanctioned events. All corners of bodies and wings must be rounded for safety. No silicone or rubber capped tires are allowed.

RACE CLASSES

NOVICE

(dirt or carpet)

To promote participation of new drivers, rules for this class are intentionally unrestricted. Most electric powered RC car/truck will be allowed. Cars/trucks will be inspected prior to racing to prevent carpet damage. Heavy (monster trucks, etc.) vehicles with rubber tires and large lugs that are likely to roll over will not be allowed. Low wind modified motors are discouraged. Drivers who exhibit sufficient skill will be encouraged to join a more advanced class. All Novice races will be 4 minutes in length.

6.0 BREAKOUT

(dirt or carpet)

THIS WILL BE A BREAKOUT LAP TIME CLASS

LAPS FASTER THAN 6.000 SECONDS WILL NOT BE COUNTED

- 1) CHASSIS - Any 1/10 scale production based 2wd/4wd chassis.
- 2) BODY - Any SC truck, rally, or car body is allowed. No extra wings, flaps or doohickeys can be added.
- 3) MOTOR - Any brushed or brushless motor allowed.
- 4) BATTERY - Up to a 2 cell LiPo hard case or max. 7 cell Nihm battery only. No hard wiring from the battery to the speed control. Must have a quick disconnect form battery.
- 5) ESC - Any commercially available ESC are allowed.
- 6) TIRES & WHEELS - Rubber street type tires are preferred. (Ask track owners about approved tire brands)
- 7) WEIGHT - No weight minimum required.
- 8) All races will be 4 minutes in length.
- 9) Maximum of 6 cars in A main. Must have (2) cars for class to run. Standing starts.

SC LATE MODEL

(dirt or carpet)

- 1) CHASSIS - Open to REAR MOTOR stock 2wd short course truck chassis. No aftermarket chassis.
 - a) Main tub or frame must be stock to the brand of truck being raced. No offset or LTO chassis will be allowed.
 - b) Traxxas low-cg chassis may be used.
 - c) After market shock towers, shocks, front and rear axle carries, Adjustable rear A-arms may be used (RPM, aluminum etc.).
 - d) Batteries must be in stock position (down the center of chassis ONLY).
 - e) Electronics can be mounted on the left side of chassis.
 - f) Up to 2oz can be added to the left side.
- 2) BODY – Late Model Bodies only, No additional wings, flaps, spoilers, wickers, vents or air devices allowed.
 - a) No metal bumpers or body parts.
 - b) A rear bumper may be added to make the appearance more realistic.
 - c) Aftermarket pieces will be allowed for bumpers and body mounting.
 - d) Front bumper must not extend past or in front of car body. The front bumper may be used as front brace (flip bumper upside down –Traxxas slash) to support body; side "bumpers" may be removed. No alterations to chassis otherwise.
- 3) REAR SPOILER - Rear spoiler can only be as wide as the body at the rear quarter panels. 3" max from deck. The end caps must be a triangle shape. You may ONLY have one fin on the spoiler and two side caps. The MID fin must also be the same dimension as side cap. The MID fin maybe located anywhere on the spoiler between the two side caps. T
REAR SPOILER - Rear spoiler can only be as wide as the body at the rear quarter panels. 3" max from deck. The end caps must be a triangle shape. You may ONLY have one fin on the spoiler and two side caps. The MID fin must also be the same dimension as side cap. The MID fin maybe located anywhere on the spoiler between the two side caps.
- 4) ESC & MOTOR COMBOS – *Hobbywing XR10 JUSTOCK ESC ONLY *Hobbywing 10.5 G2.1 [FTM] Fixed timing motor ONLY.
- 5) BATTERY – - Any 2 cell Lipo **hard case only** with a capacity not greater than **5200MAH/50C**.
 - a) **Must have "VIP" installed (see general rules)** ROAR charge limits of 8.44 volts. Must use quick disconnect connector (NO hard wiring).
- 6) TIRES & WHEELS - Tires/wheels – Any rubber tire. Must be 2.8 dia. wheel/rim or larger. SC truck 2.2"/3" tires and wheels are allowed. No 2.2 dia. tires. Must be Non aggressive street tread or slick type tires. No pin tires. No grooving or siping of the tires.
- 7) WEIGHT – No weight minimum required.

BIG BLOCK MODIFIED

(dirt or carpet)

- 1) CHASSIS – Only Traxxas Slash 2-wheel-drive truck chassis only. No aftermarket chassis.
 - a) Traxxas low-cg chassis may be used.
 - b) Batteries must be in stock position (down the center of chassis ONLY).
 - c) Aftermarket parts are allowed – RPM transmission case, steering mechanism, shock towers, shocks, front and rear axle carries, etc. (RPM, aluminum etc.).
- 2) BATTERY - Any 2 cell Lipo **hard case only** with a capacity not greater than **5200MAH/50C**.
 - a) **Must have "VIP" installed (see general rules)** ROAR charge limits of 8.44 volts. Must use quick disconnect connector (NO hard wiring).
 - b) Labels on battery must be readable, No tape on batteries labels or any signs of tampering with labels. No bare wires, wires must be covered.
- 3) ESC & MOTOR – *Hobbywing XR10 JUSTOCK ESC ONLY *Hobbywing 10.5 G2.1 [FTM] Fixed timing motor ONLY.
- 4) TIRES & WHEELS – Any rubber buggy tire. Must be 2.2 or 2.4 dia. buggy style wheel/rim.
 - a) Must be Non aggressive street tread or slick type tires. No pin tires.
- 5) BODY – Must be mudboss style body only. No metal bumpers or body parts.
 - a) Body must be offset like real world Big Block Modified's
 - b) Left rear tire must be inside left body panel. A maximum of ¼ inch of the left rear tire may extend outside of the left body panel.
 - c) Body must be mounted straight or in line with chassis.
 - d) Front and rear bumpers are allowed. Must be stock in appearance to the Big Block Modified style race cars. Front bumper must not extend past front body panel/hood more than ¾ of an inch on all sides of hood.
 - e) Side "bumpers" may be removed. No alterations to chassis otherwise.
- 6) Maximum of 6 cars in A main. Must have (2) cars for class to run. Rolling starts.

MUDBOSS/SC B MOD

(dirt or carpet)

- 1) CHASSIS – Only Traxxas Slash 2-wheel-drive truck chassis only. No aftermarket chassis.
 - a) Traxxas low-cg chassis may be used.
 - b) Batteries must be in stock position (down the center of chassis ONLY). No shorty packs.
 - c) Only stock Slash 2wd Original manufacturer chassis and suspension parts only. All parts must be in stock position and location. (No RPM, no aluminum etc.).
 - d) Front and rear bumpers are allowed. Must be stock in appearance to Modified or EDM race cars. Front bumper must not extend past front body panel/hood more than $\frac{3}{4}$ of an inch on all sides of hood. The stock front bumper maybe used as a front brace (flip bumper upside down) to support front body panel/hood. Side "bumpers" may be removed. No alterations to chassis otherwise.
 - e) Must use Traxxas Slash "stock" shocks and, Traxxas Slash "stock" white springs only and in the appropriate place. (front on front, rear on rear)
 - f) Shock internal limiters may be installed. No front bump stops suspension. A single original blue bump stop can be used per rear shock (not mandatory).
- 2) BATTERY - Any 2 cell Lipo **hard case only** with a capacity not greater than **5200MAH/50C**.
 - a) **Must have "VIP" installed (see general rules)** ROAR charge limits of 8.44 volts. Must use quick disconnect connector (NO hard wiring).
 - b) Labels on battery must be readable, No tape on batteries labels or any signs of tampering with labels. No bare wires, wires must be covered.
- 3) ESC & MOTOR - ROAR APPROVED Sportsman ESC, ESC must be in Blinky Mode. ROAR APPROVED 13.5 2 pole sensed motor.
- 4) TIRES & WHEELS – Any rubber tire. Must be 2.8 dia. wheel/rim or SC truck 2.2"/3" tires and wheels are allowed. No 2.2 dia. tires. Must be Non aggressive street tread or slick type tires. No pin tires. No grooving or siping of the tires.
- 6) GEARING - No gear rule.
- 7) BODY - Any modified or mudboss style bodies only. No metal bumpers or body parts.
- 8) Maximum of 6 cars in A main. Must have (2) cars for class to run. Rolling starts.

SC MOD

(dirt or carpet)

- 1) CHASSIS - Open to stock 2wd short course truck chassis.
 - g) Main tub or frame must be stock to the brand of truck being raced. No offset or LTO chassis will be allowed.
 - h) Aftermarket chassis allowed I.E. carbon fiber, aluminum, etc.
 - i) Batteries must be in stock position (down the center of chassis ONLY).
 - j) Electronics can be mounted on the left side of chassis.
 - k) Up to 2oz can be added to the left side.
- 2) BODY – Only modified style bodies allowed. No truck bodies will be allowed.
 - a) A front and rear bumper may be add to make the appearance more realistic.
 - b) Aftermarket pieces will be allowed for bumpers and body mounting.
- 3) MOTOR – 13.5 ROAR APPROVED 2 pole motors only.
- 4) ESC – ESC - Any ROAR APPROVED Sportsman ESC or ESC in a sportsman setting is allowed. (Blinky Mode)
- 5) BATTERY – Any 2 cell max. Lipo hard cased battery only.
 - a) **Must have "VIP" installed (see general rules)**. ROAR charge limits of 8.44 volts.
- 6) TIRES & WHEELS - Tires/wheels – ONLY SC truck 2.2"/3" tires and wheels are allowed. Must be Non aggressive street tread or slick type tires. No pin tires. No grooving or siping of the rubber tires.
- 7) WEIGHT – No weight minimum required.

1/10 SCALE LATE MODEL

(carpet only)

- 1) DODC.com Late Model rules apply.
- 2) MOTOR – 17.5 ROAR APPROVED 2 pole sensed motors only.
- 3) BATTERY – Any 2 cell max., 7.4V Lipo battery hard cased battery.
 - a) **Must have "VIP" installed (see general rules).**
- 4) TRAN. – Open
- 5) ESC - Any Sportsman ESC/ ESC in a sportsman setting is allowed. (Blinky Mode)
- 6) TIRES & WHEELS – Any foam tire that fits within the DODC rules for foam tires. No pan car tires.
- 7) WEIGHT – 53 oz. minimum with transponder before or after the race.
- 8) 2" rear spoiler maximum.
- 9) See DODC.com for any other Late Model rules.
- 10) Maximum of 6 cars in A main. Must have (2) cars for class to run. Rolling starts.

360 SPRINTS

(dirt only)

- 1) DODC.com Sprint Car chassis, body & wing rules apply.
- 2) Small front wing (8 sq in.) is allowed. 6" x 6" Top Wing is the maximum size allowed.
- 3) MOTOR – 17.5 ROAR APPROVED 2 pole motors only.
- 4) ESC - Any ROAR APPROVED Sportsman ESC or ESC in a sportsman setting is allowed. (Blinky Mode)
- 5) BATTERY – Any 2 cell max. Lipo hard cased battery only.
 - a) **Must have "VIP" installed (see general rules)** ROAR charge limits of 8.44 volts only.
- 6) TRAN. – Open
- 7) TIRES & WHEELS - Any 2.0 "Custom Works" or 2.2 "buggy" rubber tire that fits within the DODC rules for Rubber Tires.
- 8) WEIGHT – 57 oz. minimum with transponder before or after the race.
- 9) See DODC.com for any other Sprint Car rules.

MIDWEST MOD

(dirt or carpet)

- 1) CHASSIS - Open to 2wd OFF ROAR BUGGY chassis only.
 - a) NO aftermarket chassis allowed I.E. carbon fiber, aluminum, etc. No offset or LTO chassis will be allowed.
 - b) Batteries must be in stock position (down the center of chassis ONLY).
 - c) Electronics can be mounted on the left side of chassis.
 - d) Up to 2oz can be added to the left side.
- 2) BODY – Only modified style bodies allowed. No truck bodies will be allowed.
 - a) A front and rear bumper maybe added to make the appearance more realistic.
 - b) Stock replacement aftermarket parts will be allowed. NO rear steer allowed beyond the stock available adjustment.
- 3) MOTOR – 17.5 ROAR APPROVED 2 pole sensed motors only.
- 4) BATTERY – Any 2 cell max., 7.4V Lipo hard cased battery only.
 - a) **Must have "VIP" installed (see general rules).**
- 5) ESC – Any Sportsman ESC/ ESC in a sportsman setting is allowed. (Blinky Mode).
- 6) TIRES & WHEELS - Any rubber tire. Must be 2.2 dia. wheel/rim or larger. Must be Non aggressive street tread or slick type tires. No pin tires.
- 7) WEIGHT – No weight minimum required.
- 8) Maximum of 6 cars in A main. Must have (2) cars for class to run. Rolling starts.

SHORT COURSE TRUCK 2wd

(dirt or carpet)

- 1) CHASSIS - Open to factory stock short course truck / rally chassis below are some examples but not limited too.
 - *Team Associated SC10 all 2wd versions
 - *Team Losi XXXSCT
 - *Team Losi 22sct
 - *HPI Blitz
 - *Kyosho SCR
 - *Venom Gambler
 - *Traxxas Slash
 - * Durango DESC210
- 2) Main tub or frame must be stock to the brand of truck being raced. No offset or LTO chassis will be allowed.
 - a) 4wd chassis maybe used but front drive axles or shafts must be disconnected.
- 3) No aftermarket woven carbon fiber chassis allowed.
- 4) Batteries must be in stock position for the chassis being used.
- 5) Electronics can be mounted on the left side of chassis.
- 6) BODY – Only SC truck style bodies allowed.
- 7) MOTOR – Open Motor.
- 8) BATTERY – Any 2 cell max., 7.4V Lipo battery hard cased battery.
 - a) **Must have "VIP" installed (see general rules).**
- 9) ESC – Open speed control.
- 10) TIRES & WHEELS - SC truck 2.2"/3" tires and wheels only. Must be rubber non aggressive street tread or slick type tires.
- 11) WEIGHT – No weight minimum required.
 - Maximum of 6 cars in A main. Must have (2) cars for class to run. Rolling starts. Any and all upgrades to the suspension are allowed. Aftermarket shocks, A-Arms, axle carriers, Etc. is allowed. If using adjustable rear A-Arms they must be set at zero. (The intent is to keep rear steer out of this class.)

STREET STOCK

(dirt or carpet)

- 1) CHASSIS - Open to 2wd OFF ROAD BUGGY chassis only.
 - a) NO aftermarket chassis allowed I.E. carbon fiber, aluminum, etc. No offset or LTO chassis will be allowed.
 - b) Batteries must be in stock position (in the center of chassis ONLY).
 - c) Stock replacement aftermarket parts will be allowed. NO rear steer allowed beyond the stock available adjustment
 - d) Electronics can be mounted on the left side of chassis.
 - e) Up to 2oz can be added to the left side.
- 2) BODY - Molded type bodies only. No added spoiler is allowed over the stock built in molded spoiler. No additional wings, flaps, spoilers, wickers, vents or doohickeys will be allowed.
 - a) Aftermarket body mounts and bumper allowed but metal bumpers or body parts are not permitted.
 - b) Decking is not allowed.
 - c) Some body type examples :
 - McAllister Racing – #264 Camaro Street Stock
 - McAllister Racing- #268 Monte Carlo Street Stock
 - McAllister Racing- #303 Fairlane 500
 - McAllister Racing- #290 69 Dodge Charger Street Stock
 - McAllister Racing- #134 1/10th 70' Barracuda Street Stock
 - McAllister Racing- #256 Firebird Street Stock
 - McAllister Racing- #125 Buick Regal Street Stock
 - McAllister Racing- #136 70' Mustang Street Stock
 - McAllister Racing- #313 427 Nova Street Stock
 - McAllister Racing- #306 Chevelle Street Stock
 - Custom Works Street Stock Camaro #CWS9075
- 4) MOTOR – 21.5 ROAR APPROVED 2 pole sensored motors only.
- 5) ESC – Any ROAR APPROVED Sportsman ESC/ ESC in a sportsman setting is allowed. (Blinky Mode).
- 6) BATTERY – Any 2 cell max. Lipo hard cased battery only.
- 7) **Must have "VIP" installed (see general rules).** ROAR charge limits of 8.44 volts.
- 8) TIRES & WHEELS – Any 2.2 buggy rubber tires. Must be Non aggressive street tread or slick type tires. No pin tires.
 - a) No rear tires on the front.
 - b) Fronts tires must be 2wd buggy tire width.
 - c) No 4wd front tires allowed
- 9) Maximum of 6 cars in the A main. Must have (2) cars for class to run. Rolling starts.

OLD COUPE

(dirt or carpet)

- 7) Must be 60 or older or by invite.
- 8) CHASSIS – Only Traxxas Slash 2-wheel-drive truck chassis only. No aftermarket chassis.
 - d) Traxxas low-cg chassis may be used.
 - e) Batteries must be in stock position (down the center of chassis ONLY).
 - f) Only Slash 2wd manufacturer suspension parts. All parts must be in stock position and location.
 - g) Allowed aftermarket parts – RPM transmission case, steering mechanism, shock towers, shocks, front and rear axle carries may be used (RPM, aluminum etc.).
 - h) Shock internal limiters may be installed. No front bump stops suspension. A single original blue bump stop can be used per rear shock (not mandatory).
 - i) Front and rear bumpers are allowed. Must be stock in appearance to the Coupe style race cars. Front bumper must not extend past front body panel/hood more than $\frac{3}{4}$ of an inch on all sides of hood. The stock front bumper maybe used as a front brace (flip bumper upside down) to support front body panel/hood. Side "bumpers" may be removed. No alterations to chassis otherwise.
- 9) BATTERY - Any 2 cell Lipo **hard case only** with a capacity not greater than **5200MAH/50C**.
 - c) **Must have "VIP" installed (see general rules)** ROAR charge limits of 8.44 volts. Must use quick disconnect connector (NO hard wiring).
 - d) Labels on battery must be readable, No tape on batteries labels or any signs of tampering with labels. No bare wires, wires must be covered.
- 10) ESC – Traxxas XL-3 or XL-5.
- 11) MOTOR – Traxxas 12T Titan motor. Labels on motor must be readable, No tape on labels or any signs of tampering with labels.
- 12) TIRES & WHEELS – Any rubber tire. Must be 2.8 dia. wheel/rim or larger. SC truck 2.2"/3" tires and wheels are allowed. No 2.2 dia. tires. Must be Non aggressive street tread or slick type tires. No pin tires. No grooving or siping of the rubber tires.
- 13) BODY - Any Coupe style body only. McAllister Racing #310, #316. No metal bumpers or body parts.
- 14) Maximum of 6 cars in A main. Must have (2) cars for class to run. Rolling starts.

STOCK SC LATE MODEL

(dirt or carpet)

- 1) CHASSIS – Only Traxxas Slash 2-wheel-drive truck chassis only. No aftermarket chassis.
 - a) Traxxas low-cg chassis may be used.
 - b) Batteries must be in stock position (down the center of chassis ONLY).
 - c) Only Slash 2wd manufacturer suspension parts. All parts must be in stock position and location.
 - d) Allowed aftermarket parts – RPM transmission case, steering mechanism, shock towers, shocks, front and rear axle carries may be used (RPM, aluminum etc.).
 - e) Shock internal limiters may be installed. No front bump stops suspension. A single original blue bump stop can be used per rear shock (not mandatory).
 - f) Front and rear bumpers are allowed. Must be stock in appearance to latemodel style race cars. Front bumper must not extend past or in front of body panel/hood. The stock front bumper maybe used as a front brace (flip bumper upside down) to support front body panel/hood. Side "bumpers" may be removed. No alterations to chassis otherwise.
- 2) BATTERY - Any 2 cell Lipo **hard case only** with a capacity not greater than **5200MAH/50C**.
 - a) **Must have "VIP" installed (see general rules)** ROAR charge limits of 8.44 volts. Must use quick disconnect connector (NO hard wiring).
 - b) Labels on battery must be readable, No tape on batteries labels or any signs of tampering with labels. No bare wires, wires must be covered.
- 3) ESC – Traxxas XL-3 or XL-5.
- 4) MOTOR – Traxxas 12T Titan motor. Labels on motor must be readable, No tape on labels or any signs of tampering with labels.
- 5) TIRES & WHEELS – Any rubber tire. Must be 2.8 dia. wheel/rim or larger. SC truck 2.2"/3" tires and wheels are allowed. No 2.2 dia. tires. Must be Non aggressive street tread or slick type tires. No pin tires. No grooving or siping of the rubber tires.
- 6) BODY - Any latemodel style body only. No metal bumpers or body parts.
- 7) Maximum of 6 cars in A main. Must have (2) cars for class to run. Rolling starts.

DLMRA - 1/8 MOD ELECTRIC LATE MODEL

(dirt only)

Chassis

- 1) Must be 1/8 production based 4 WD buggy drive train. (Losi, Ofna, X-Ray and so on)
- 2) No offsetting a-arms or narrowing of a-arms.
- 3) Must have dog bone center drive train, no on-road drive trains.
- 4) No interchanging of manufactures drive train parts. (Losi must use Losi drive train and so on)
- 5) No third channel devices (no one wheel brakes, wing adjustments and so on)
- 6) Wheel base: 12 5/8" to 13".
- 7) Width: 13" max. - 11 1/4" min.
- 8) Any and all parts must be flush or inside the tread width. 1/8 tolerance.
- 9) All chassis and tires must remain inside the body.
- 10) No metal or carbon fiber front bumpers.
- 11) Must have foam on the front bumper.

Motors, Batteries & Speedo

- 1) 2250 KV or less brushless motor. 4 pole or less
- 2) Motor must have factory marked KV rating on can/ endbell.
- 3) Open Speedo.
- 4) Any hard case 4 cell lipo.
 - a) Must have hobby grade connector!
 - b) Must be hard case lipo's! Covers/ cases over soft cell packs accepted.
 - c) ROAR charge limit! 4.22 per cell max.

Bodies

- 1) Molded one-piece bodies are preferred.
- 2) No additional wings, flaps, spoilers, wickers, vents or doohickeys will be allowed except what's in sections 4 & 5.
- 3) A hole or holes for motor cooling.
- 4) Decking is allowed.
- 5) There will be no metal body parts of any kind.
- 6) All bodies must be approved.

Side Dam specs

- 1) Side dam is NOT Allowed

Rear Spoiler Specs

- 1) Rear spoiler can only be as wide as the body at the rear quarter panels.
- 2) Rear spoiler 3" max from deck.
- 3) The end caps must be a triangle shape.([See template](#)) You may have one fin on the spoiler and two side caps. The third fin must also be the same dimension as side cap. It can be located anywhere on the spoiler between the two side caps. The fin must be in line with the side caps on the front leading edge.

Wheel & Tire Specs

- 1) Rubber tires only
- 2) All wheels must be 17mm buggy based.
- 3) There will not be any grooving or sipping of the rubber tires.
- 4) Any street tread type 1/8 rubber tire.
- 5) Traction compounds are legal.

Weight

- 1) 7-1 8 lb Minimum, 11 lb Maximum.

OTHER CLASSES

(4) or more drivers may create a new class of racing if their cars do not fit in an existing DFRCR track class. Other classes may be proposed such as Stadium Truck, Gearbox etc. if (4) or more drivers want to race in a new class. All new classes will only be eligible for point racing after a class name and rules have been developed and approved by the DFRCR Board of Directors. Cars/trucks running in a new class must have approved tires and chassis may not have protruding screws or sharp edges that may damage the track. Check our Web Site (www.DFRCR.com) for latest rule updates.
Revised: March 5, 2016

This area is for anyone to use to suggest a new class to DFRCR and list all of the rules for that class.

Class name: _____

Name: _____
(SPOKESPERSON FOR THE CLASS)

Class rules:

Signed: _____ DATE _____

Signed: _____ DATE _____

Signed: _____ DATE _____

(Signature from DFRCR)